



RED BOX
INTERNATIONAL®

MODEL RB25A

HAND / AIR PORTABLE POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES



NATO S/N 2995-99-132-3061

Max amps.	800 (Nom. short circuit current)
Capacity.	16 Amp Hrs @ 10hr rate
Max voltage.	26v DC
Size.	L350 W90 H230 mm
Weight.	16 Kg
Operating Temp.	-40° C - + 60° Celsius
Case.	Stainless steel
Voltage Indication.	Digital to IP65
Auxiliary Protection.	Circuit breaker 20A
Auxiliary Input.	29v DC
Aircraft Cable.	1.5 Metre heavy duty
Charger.	3 Amp Electronic universal AC input
Protection.	Reverse polarity warning

Accessories

50 or 100 Amp 28vDC Power Supply
Parallel joining cable

Specification may change without notice

- Totally weather protected.
- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- No memory effect.
- Works in any orientation.
- High charge retention.
- Long shelf life.
- Fast recharge.
- No cycling.
- Leak proof.
- Cells replaceable on condition.
- Light duty engine starting of turbo prop, turbine, aircraft and helicopters.
- Starts Armoured Fighting Vehicles.
- Lightweight portable start power at remote locations.

The RB series is in use with NATO, and other Militaries

www.redboxpower.com Tel +44 (0) 1794 518888 Fax +44 (0) 1794 518848 sales@redboxpower.com